

# SPIRENT GSS4200

## GPS PRODUCTION/FIELD TEST MULTI-CHANNEL SIMULATOR

The Spirent GSS4200 provides full navigation test capability in a production/field test environment. Designed specifically for easy ATE integration via the IEEE-488, the Spirent GSS4200 represents an attractive choice for high volume test environments.

### Key Features

- 6 channels GPS L1 C/A code
- Allows position fix with representative satellite dynamics and data
- Single channel mode
- Supplied with a range of selectable test scenarios designed to meet production test requirements
- Integrates easily with production line ATE via IEEE-488, USB or RS232
- Wide dynamic range with output power levels as low as  $-155\text{dBm}$
- Calibrated high and low power RF output ports

As navigation-based GPS solutions proliferate and become more demanding, the need for a multi-channel GPS simulator in a production environment becomes increasingly important.

The Spirent GSS4200 provides easy integration with a customer's test environment via standard IEEE-488, USB or RS232 interfaces. The GSS4200 also supports synchronisation to other systems via its Trigger, Frequency Standard and 1PPS outputs/inputs.

For users needing the flexibility to switch between single channel and multi-channel test modes, the GSS4200 unit offers the functionality of Spirent's GSS6300 single channel signal generator. For assisted GPS applications, the assistance data for each scenario is provided as standard.

The GSS4200 retains Spirent's industry leading accuracy, fidelity and reliability. Run to run stability is within 0.1dB with low phase noise and high frequency stability. The GSS4200 can be calibrated in-situ, minimising down time and disruption.

For A-GPS wireless protocol conformance test applications, the GSS4200 provides an ideal GPS signal source.



Multi-Channel Production/Field Test Simulator: Spirent GSS4200

# SPIRENT GSS4200

## GPS PRODUCTION/FIELD TEST MULTI-CHANNEL SIMULATOR

### SPECIFICATION

#### Output Frequency

- L1 @ 1575.42MHz

#### Channels

- Number 6
- Type GPS C/A code @ 50 bps

#### Signal Dynamics

- Max Velocity ±1000m/s

#### Signal Accuracy

(RMS max over 1 minute)

- Pseudorange ±10cm
- Pseudorange rate ±1cm/s
- Delta-Pseudorange ±5mm
- Interchannel bias Zero

#### Signal Quality

- Spurious (Max) - 30dBc
- Harmonics (Max) - 35dBc
- Phase Noise (Max) 0.02 rad RMS (10Hz-10kHz offset)
- Frequency Stability ±1x10<sup>-9</sup>per day

#### Signal Level

- Low power output - 130dBm nominal, front panel
- High power output - 70dBm nominal, front panel  
±0.1dB run-to-run (-25dB to +10dB)

#### Signal Level Control (both outputs simultaneously)

- Range + 10/-25dB
- Resolution 0.1dB
- Calibration Accuracy ±0.7dB RSS  
±0.1dB run-to-run  
(-25dB to +10dB)

#### Signal Generator Unit

- Channel type GPS C/A with data @ 50bps
- Size (HxWxD) 89 x 449 x 386mm  
(3.5 x 17.75 x 15.25inch)  
480mm (19inch) desktop/ rack  
mount case
- Weight 5.5kg (12lb.)
- Power 100 - 264V, 48-62 Hz

#### Product Specification (MS3013) is available on request

Performance figures and data in this document are typical and must be specifically confirmed in writing by Spirent Communications plc. before they become applicable to any particular order or contract.

The publication of information in this document does not imply freedom from patent or other rights of Spirent Communications plc. or others.

For current product data, visit the Spirent websites at [www.spirent.com/positioning](http://www.spirent.com/positioning) or [www.spirentfederal.com](http://www.spirentfederal.com)

### SALES AND INFORMATION

Spirent Communications plc, Aspen Way, Paignton, Devon TQ4 7QR, UK  
T: +44 1803 546325 [globalsales@spirent.com](mailto:globalsales@spirent.com) [www.spirent.com/positioning](http://www.spirent.com/positioning)

US Government & Defense: Spirent Federal Systems Inc. 22345 La Palma Avenue, Suite 105, Yorba Linda, CA 92887  
T: +1 714 692 6565 [info@spirentfederal.com](mailto:info@spirentfederal.com) [www.spirentfederal.com](http://www.spirentfederal.com)



© 2012 Spirent Communications plc. All of the company names and/or brand names and/or product names referred to in this document, in particular the name "Spirent" and its logo device, are either registered trademarks or trademarks pending registration in accordance with relevant national laws. All rights reserved. Specifications subject to change without notice.